

INDUSTRIAL GRADE DEGALVANIZER

1139 COATING SOLUTION

FLASH POINT 123.8°F

DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES SERIOUS EYE IRRITATION. MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

Contains: Kerosene 8008-20-6, Glycol Ether EP 2807-30-9. OTHER INGREDIENTS: "Contents Partially Unknown", Petrolatums.



Danger! Flammable liquid and vapor. Harmful if swallowed. May cause damage to organs through prolonged or repeated exposure.

Prevention: Use only with adequate ventilation. Do not breathe dust/vapors/spray mist. Avoid contact with eyes/skin/clothing. Wear protective gloves/clothing/glasses. Keep away from heat/sparks/open flames/hot surfaces. Do not eat/drink/smoke when using this product. Ground/bond

container and receiving equipment. Take precautionary measures against static discharge. Use only non-sparking tools.

Response: In case of fire, use extinguishing powder or water spray. Immediately contact a doctor or POISON CONTROL CENTER if you feel unwell. If medical attention is needed, have product label at hand. IF IN EYES: Rinse with water for several minutes. Remove contact lenses if present. If eye irritation persists seek medical attention. IF SWALLOWED: Rinse mouth with water. Do not induce vomiting. IF INHALED: Remove to fresh air. IF ON SKIN: Wash thoroughly with water. Remove all contaminated clothing.

Storage: Keep container tightly closed. Store in a well ventilated place. Keep cool. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F.

Disposal: Dispose of product in accordance with local/regional/national/international regulations.

Additional Precaution Statements: Vapors may ignite explosively and cause a flash fire. Prevent buildup of vapors by opening windows and doors to achieve cross ventilation. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately inhaling the contents may be harmful or fatal. In cases where short and/or long term overexposure conditions exist, a charcoal filter respirator should be worn. Follow respirator manufacturer's directions for use.

TECHNICAL DATA:

STORAGE TEMPERATURE: 40°F-100°F

OPERATING SPEED: <500 RPM

HIGH TEMPERATURE RESISTANCE: 150°F

LOW TEMPERATURE RESISTANCE: -20°F

HAPS CONTENT: 3.6%

SOLIDS CONTENT: 12.4%

WPG: 6.89lbs/gal.

CLEAN UP: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust.

FOR INDUSTRIAL USE ONLY

READ MATERIAL SAFETY DATA SHEET BEFORE USING THIS PRODUCT

KEEP OUT OF REACH OF CHILDREN

Manufactured For:



www.1987machinery.com

4300 Shady Ln., Huntingtown, MD 20639



**INDUSTRIAL GRADE
DEGALVANIZER**